

TriXon

Sweep < Scrape < Bedding



TriXon – Effective stall cleaning

Reliable barn machine for scraping, sweeping and bedding



Agro X • Lysemosen 8 • DK-8600 Silkeborg • Tlf. 86 87 76 88 • www.agrox.dk

Importer in Canada Protekta Inc. • ph. 519 528 5888 • email: Protekta@protekta.ca • www.protekta.ca

Build strong – Great reliability

Trixon is build strong on an articulating frame, which makes it very maneuverable in the barn. Build only with high quality materials.

Trixon is mounted with large tires (508 mm x 213 mm) with great grip. It gives the machine a large clearance and enables it to manage most obstacles in the barn.

The engine is a strong 18 HP, three cylinders, water-cooled diesel engine, with a low noise level. No drive belts etc. ensures low maintenance!

Forward and reverse drive is done by a hydrostatic pump via two pedals (one for left foot and one for right foot). This gives the driver greater control and feeling with the machine.

All functions on the Trixon are hydraulic and are controlled by two pumps. This ensures that all functions on the machine can be used at the same time.

The dosing auger in the bottom of the hopper secures that the bedding material is dosed uniform in to the blower.

The blower and the dosing auger can be adjusted individual and the blower is build of heavy material and works well with both shavings, straw, and other bedding materials.



Cleans quick and efficient

Low operating cost, High earnings



The hopper is also hydraulic controlled for easy filling



Loading directly from pile of bedding.



The large tires allows for the Trixon to drive in rough terrain



The scraper has replaceable rubber on the bottom and is adjusted by hydraulic.



The broom diameter is 800 mm (31 inches) and is hydraulic adjusted both up and down and to the sides. This ensures effective cleaning in all corners.

The blower is variable adjusted to fit any demand of material. Easy to adjust flaps secure the placing of bedding correct.



Trixon is equipped with a heavy-duty blower with 6 mm wings and with lots of space between the fan blade and fan housing. This reduces the risk of damages to the blower due to stones etc.



Safety bolts on the side broom to protect against damage if broom hits stalls or walls.



TrixKon

Sweep < Scrape < Bedding



Specifications:

	Trixon 4500	Trixon 4800
Width at front wheels	940 mm or 37"	940 mm or 37"
Width at rear wheels	930 mm or 36"	930 mm or 36"
Length w/o broom	2750 mm or 108"	2750 mm or 108"
Length w/ broom	3000 mm or 118"	3000 mm or 108"
Width w/o broom	940 mm or 37"	1140 mm or 45"
Width w/ broom	1160 mm or 45"	1360 mm or 54"
Height	1710 mm or 67"	1710 mm or 67"
Height w/ ext. top	1750 mm or 70"	1750 mm or 70"
Capacity	630 liter or 176 gal	770 liter or 203 gal
Capacity w/ ext. top	830 liter or 219 gal	1020 liter or 269 gal

Options available: 4 WD drive
Bedding additive dosing unit